



仕樣	單位	CXMG-150
合模力	kN	1500
動模行程	mm	380
裝模板尺寸 (豎×橫)	mm	
連接柱內尺寸 (豎×橫)	mm	460×460
模具最大厚/最小厚	mm	500/200
連接柱徑	mm	
頂出力	kN	87
頂出行程	mm	90
射出力	kN	83
射出行程	mm	200
射出柱塞直徑	mm	Φ60/Φ65
噴嘴接嘴力	kN	72
噴嘴接嘴行程	kN	250
鑄造壓力	MPa	29.7
可鑄面積 (效率100%)	cm ²	496
可鑄重量 (效率60%)	g	610
常用壓力	MPa	10.5
電動機容量	kw	18.5
操作電源容量	kVA	27.5
坩鍋容量	kg	250
油缸容量	L	
機械重量	ton	8.5



CXMG-600



可動盤 MOVABLE PLATEN



固定盤 FIXED PLATEN



CXMG-60/150/250/350 (mm)

	CXMG-60	CXMG-150	CXMG-250	CXMG-350
[1]	488	720	870	950
[2]	330	460	530	600
[3]	65	100	125	150
[4]	58	85	110	125
[5]	4500	5000	5400	6675
[6]	2000	2550	2550	2570
[7]	2350	2520	2780	3100

